

Christie LX41/LW41

Corporate AV
Government
Healthcare
Higher education
Houses of worship



Performance, features and value

The Christie® LX41 and Christie LW41 provide bright, affordable options in XGA and WXGA resolutions that meet the ProAV feature requirements in today's small to medium-sized venues. These models are ideal for corporate meeting rooms, classrooms, training rooms, houses of worship or any application that requires a full-featured portable projector in the 4000 ANSI lumens range. These models feature LAN network connectivity, and various plug and play integration options.

With flexible installation needs in mind, these projectors ship standard with an extended range 1.7 x manual zoom lens and horizontal and vertical lens shift to help simplify installation. As with all Christie 3LCD products, the Christie LX41 and Christie LW41 are backed by a three year warranty and Christie's renowned service and support.

CHRISTIE®

		LX41 (121-011103-01)	LW41 (121-010102-01)
Image	brightness	• 4000 ANSI lumens	
	contrast	• 2000:1 full on/full off	
Display technology	type	• 3 x 0.63" Inorganic LCD	• 3 x 0.59" Inorganic LCD
	native resolution	• 1024 x 768 XGA	• 1280 x 800 WXGA
Lamp	type	• 245W UHB	
	estimated life	• Normal mode: up to 3000 hrs • Eco mode: up to 5000 hrs	
Input	signals	• SDTV: 480i, 480p, 576i, 576p • HDTV: 720p @ 50/60Hz, 1080i @ 50/60Hz, 1080p @ 50/60Hz • VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA, MAC 16"	
	scan rates	• 27-162 MHz (see user's manual for detail information)	
Inputs/ outputs, control and networking	input	• Video Input: S-video – Mini Din 4 pin x 1; Composite video – RCA x 1; Component video – RCA x 3 • Audio Input: 3.5 mini x 2 RCA x 2 (L/R) • Computer Input: D-Sub 15 pin x 1; BNC x 5 • HDMI Input: HDMI x 1 (HDCP compliant) • USB: USB type A x1 for PC-Less presentation; USB type B x 1 for USB display or mouse control • LAN: RJ45 x 1 wired network • Microphone Input: Mono 3.5 mini x 1 (Dynamic and unbalanced microphone)	
	control	• RS-232C 9 pin D-Sub	
	output	• Output: D-Sub 15 pin (monitor out) • Audio Out: RCA (L,R)	
Optical system		• Standard lens included – 1.7 x zoom lens • Manual zoom and focus (1.5-2.5:1 throw ratio)	
Lenses	standard	• 1.5-2.5:1 throw ratio, zoom and focus	
	keystone	• Automatic and manual keystone • Horizontal: ±30 degrees • Vertical: ±30 degrees ¹	
Accessories	standard	• Computer cable • Remote control • Lens cover • Power cord • User manual • Security label	
	optional	• Lamp (003-120730-01) • Hybrid filter (003-004239-01)	
Enhanced feature sets		• AMX Device Discovery; blackboard/whiteboard mode • Daytime mode • 3D Keystone™ geometry correction • Closed caption (NTSC and component 480i only) • Stackable ² • Text message capabilities via network • 16W Mono speakers	
Power requirements	operating voltage	• 100-120 VAC ±10% • 200-240 VAC ±10%	
	operating current	• 50A @ 100-120V • 100A @ 220-240V	
	consumption	• 380W AC100-120V @ 50/60Hz • 360W AC220-240V @ 50/60Hz	
	dissipation	• 1292 BTU/hr @ 100-120V • 1224 BTU/hr @ 220-240V	
Dimensions	size	• (LxWxH): 12.5 x 15.8 x 4.6" (318 x 401 x 118mm)	
	shipping size	• (LxWxH): 16.5 x 22.0 x 7.8" (420 x 560 x 197mm)	
	weight	• 10.6lbs (4.8kg)	
	shipping weight	• 18.1lbs (8.2kg)	
Noise		• Standard mode: 36dBA • Eco mode: 30dBA	
Operating environment		• Temperature: 41-95°F (5-35°C) • Humidity (non-condensing): Operating 10-85%, Storage 10-85%	
Regulatory approvals		This product conforms to the following regulations related to product safety, environmental requirements and electromagnetic compatibility (EMC) • FCC, Part 15, Subpart B, Class A • EN55022/CISPR22 Class A • EN55024/CISPR24 • IEC 60950-1 • UL 60950-1 • CAN/CSA C22.2 No. 60950-1 • Directive (EC) 2002/95/EC (RoHS) • Directive 2002/96/EC (WEEE) • EU Regulation (EC) No. 1907/2006 (REACH) • Certifications marks (check with Christie for latest update): cULus (Canada & US), CE (EU), CCC (China), GoST-R (Russia), C-Tick (Australia & New Zealand), South Africa	
Limited warranty		• Projector: three years parts and labor • Lamp: 120 days or 500 hours (whichever comes first) • Contact an authorized Christie representative for full details of our limited warranty	

¹ 3D digital keystone (geometry correction).

² In a stacked setup, this projector is best suited for events or temporary use.

The projector may need to be re-aligned if it is used in a fixed-installation application.

Corporate offices

Christie Digital Systems USA, Inc
USA – Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Canada – Kitchener
ph: 519 744 8005

Worldwide offices

United Kingdom
ph: +44 (0) 118 977 8000

Germany
ph: +49 2161 664540

France
ph: +33 (0) 1 41 21 44 04

Spain
ph: +34 91 633 9990

Eastern Europe and
Russian Federation
ph: +36 (0) 1 47 48 100

United Arab Emirates
ph: +971 4 3206688

India
ph: +91 80 6708 9999

Singapore
ph: +65 6877 8737

Independent sales consultant offices

China (Shanghai)
ph: +86 21 6278 7708

China (Beijing)
ph: +86 10 6561 0240

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Italy
ph: +39 (0) 2 9902 1161

South Africa
ph: +27 (0) 317 671 347



For the most current specification information, please visit www.christiedigital.com

Copyright 2012 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 3354 Jul 12

CHRISTIE®