

4K550ST

True to life detail - 4K Ultra HD projector



- Short throw lens
- 4K UHD resolution with HDR10
- Bright 4500 lumens
- 10% vertical lens shift

Bring the benefits of high brightness Ultra HD and short throw to your projection installation. The Optoma 4K550ST delivers impressive 4K UHD images at an amazing 4500 lumens. These high-end specifications along with true to life colour reproduction capabilities bring life and clarity to any presentation.

Specifications

Display(mange) UP Display technology U.P Resolution UHD (3840/2160) Brightness 4,500 kmens ANSI brightness 4,500 kmens Contrast ratio 10,000-1 Native aspect ratio 16-9 Aspect ratio - compatible 43,16-9 Horizontal scan rate 21 - 135K/tz Vertical scan rate 21 - 120kr2 Uniformity 75%. Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp Info Light source type Light source type Lamp Lamp wats 330 Lamp wats 330 Contrope Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Connections Inputs 1 x HDM, 1 x HDM//HL, 1 x VGA, 1 x Mic Simm, 1 x Audio 3.5mm, 1 x Audio 3.5mm, 1 x SPDIF, 2 x Speaker Connections Inputs 1 x HDM, X HDM//HL, 1 x VGA, 1 x Mic Simm, 1 x Audio 3.5mm, 1 x SPDIF, 2 x Speaker Noise level (typical) 32d8		
Resolution UHD (384/02/160) Brightness 4,500 lumens ASIS brightness 4,500 lumens Contrast ratio 10,000-1 Native aspect ratio 16-9 Aspect ratio - compatible 43,16-9 Horizontal scan rate 21 - 135Khz Vertical scan rate 21 - 120Hz Uniformity 75% Screen size 0.73m - 7.63m (28.98in - 300.46in) Lamp info Lamp Light source type Lamp Lamp unifie (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Ecol, 5000 (Eco+) Optical OrRel Throw ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Lams shift Verical +10, % Native offset 100% 11.66 Lens shift Verical +10, % Native offset 100% Connectivity Connectivity Connectivity Connectivity Connectivity Somm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x Outputs 1 x Audio 3.5mm, 1 x SiPDIF, 2 x Speaker General Noise level (typical) Noise level (typical) 32dB PC compatibility UHD, WURGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VXGA, MC, ADD, XGA, SYGA, VXGA, MC, ADD, XGA, SYGA, VXGA,		
Brightness 4,500 lumens ANSI brightness 4,500 lumens Contrast ratio 10,000 1 Native aspect ratio 16:9 Aspect ratio - compatibile 43,16:9 Horizontal scan rate 24 - 120Hz Uniformity 75% Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp info Light source type Light source type Lamp Lamp life (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Verical +10, % Native offset 100% Lens shift Verical +10, % Native offset 100% Connectivity Connectivity Connectivity UBP, WOHD, WUXGA, FHD, UXGA, SKGA, WXGA, HD, XGA, SKGA, WXGA, HD, XGA, SKGA, WXGA, HD, XGA, SKGA, WXGA, HD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, HD, XGA, SKGA, WXGA, HD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, HD, XGA, SKGA, WGA, HD, XGA, SKGA, WGA, HD, XGA, SKGA, WXGA, HD, XGA, SKGA, WGA, MD, XGA, SKGA, WGA, HD, XGA, SKGA,		
ANS brightness 4.500 lumans Contrast ratio 10,000:1 Native aspect ratio 16:9 Aspect ratio - compatible 43,16:9 Horizontal scan rate 24 - 120Hz Uniformity 7% Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp valts 330 Lamp life (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical Optical Throw ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Verical + 10, % Native offset 100% Connections Inputs 1 × HOM(1 Hz VGM, 1 × MG, 1 × Moc Somm, 1 × Audio 3.5mm, 1 × USB-A power 15A, 1 × USB-A service, 1 × HJ45, 1 × 120 (MMHL, 1 × VGA, 1 × Moc Sole level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, WGB (Store)(Store)(DH2, 1 WGB)(Store)(DH2, 1 WGB, 2 WGB, 1 WGB, 1 WGB, 1 WGB, 2 WGB, 2 WGB, 1 WGB, 2 WGB, 2 W		UHD (3840x2160)
Contrast ratio 10.000:1 Native aspect ratio 10.9 Aspect ratio 10.9 Aspect ratio 31 – 135/kbz Vertical scan rate 21 – 125/kbz Uniformity 75% Screen size 0.73m - 7.83m (28.89in - 300.46in) Lamp infe (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical ±10.% Native offset 100% Connectivity Inputs 1 x HDMI/MH=L, 1 x VGA, 1 x Mic Connectivity Inputs 1 x HDMI/MH=L, 1 x VGA, 1 x Mic Connections Inputs 1 x HDMI/MH=L, 1 x VGA, 1 x Mic Sciemeral 32dB PC compatibility UHD. WOHD. WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VGA, Mac 2D compatibility UHD. WOHD. WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VGA, Mac 2D compatibility 1204/z Frame Sequential (Max. 1920x1080 1204z) 3D compatibility 1204/z Frame Sequential (Max. 1920x1080 1204z) 3D compatibility 1204/z Frame Sequential (Max. 1920x1080 1204z)	-	
Native aspect ratio 16:9 Aspect ratio - compatibile 4.3, 16:9 Horizontal scan rate 24 - 120Hz Vertical scan rate 24 - 120Hz Uniformity 75% Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp pinfo Lamp Lamp valts 330 Dybical 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x PuA5, 1 x 12W (ager, 1 x R5232) Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, WXGA, HD, XGA, SVGA, VXA, Mac 2D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz)	-	4,500 lumens
Aspect ratio - compatible 43,16.9 Horizontal scan rate 31 - 135Khz Vertical scan rate 24 - 120Hz Uniformity 75% Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp info Lamp info Lamp kits 330 Simm (14) 3400 (Eco), 5000 (Eco+) Optical 0.782:1 Throw ratio 0.5m - 5.2m Zoon type Fixed Focal length (mm) 11.68 Lens shift Vertical +10.% Connectivity Connectivity Connectivity <		
Horizontal scan rate 21 – 135Khz Vertical scan rate 24 – 120Hz Uniformity 75% Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp info Lamp info Lamp info Lamp info Lamp info Lamp info Lamp watts 330 Lamp life (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical Trow ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Lans shift Vertical +10, % Native offset 100% Connections Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HdA, 1 x IV Hager, 1 x RES22 Outputs 1 x HDMI, 1 x HDMI, 1 x HDMI, 7 x JGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HdA, 1 x IV Hager, 1 x RES22 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HdA, 1 x IV Hager, 1 x RES22 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HdA, 1 x IV Hager, 1 x RES22 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HdA, 1 x IV Hager, 1 x RES22 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HdA, 1 x IV Hager, 1 x RES22 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HdA, 1 x IV Hager, 1 x RES22 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x HadA, 1 x IV Security X Hap, 720(50/60Hz), 1080(50/60Hz), 30 compatibility 102(Fz Frame Sequential (Max, 1920x1080 120Hz), 30 s0 ready Security Security Securital (Max, 1920x1080 120Hz), 30 compatibility Securital function Securitation Securit		
Vertical scan rate 24 - 120Hz Uniformity 75% Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp info Lamp Light source type Lamp Lamp watts 330 Lamp life (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical + 10, % Native offset 100% Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic S.Smm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x XUBB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x XUBB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x XUBB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x XUBB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x XUBB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x XUBB-A power 1.5A, 1 x USB-A service, 1 x R45, 1 x 12V trigger, 1 x R5232 Socompatibility		
Uniformity 75% Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp info Lamp watts Lamp info (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical + 10, % Native offset 100% Connectivity Connectivity Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x USB-A service, 1 x PuBJS, 1 x YUIgger, 1 x RE322 Outputs 1 x Audio 3.5mm, 1 x USB-A service, 1 x PuBJS, 1 x YUIGger, 1 x RE322 Outputs 1 x Audio 3.5mm, 1 x SPDIF, 2 x Speaker General Scam, 5 x A, VGA, Mac Noise level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D compatibility 120Hz Frame Sequential (M		
Screen size 0.73m - 7.63m (28.89in - 300.46in) Lamp info Light source type Lamp watts 330 Lamp life (hours) 3000 (Bight), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical 0.782:1 Throw ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Lens shift Yes - ((downloads_link)) Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic Connections Inputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V fingger, 1 x RS232 Usbr-A service, 1 x RJ45, 1 x 12V fingger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 120bc/05/061/2, 120b(05/061/2),		
Lamp unifo Lamp using Lamp using 330 Lamp using 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10.% Native offset 100% Lens shift Vertical +10.% Connections Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic .05m - 4.0000, 0.5.mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x PJ45, 1 x 120 mgger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x PJ45, 1 x 120 mgger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x PJ45, 1 x 120 mgger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x PJ45, 1 x 120 mgger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x PJ45, 1 x 120 mgger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x		
Light source type Lamp Lamp watts 330 Lamp life (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical Throw ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Lens shift Yes - {(downloads_link]} Connectivity Connectivity Connectivity Connections Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS222 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 22 Compatibility 24 80/v, 576/v, 720y(50/K0Hz), 1080(50/K0Hz), 20 compatibility 20 LPL Frame Sequential (Max, 1920x1080 120Hz) 30 Gompatibility 20 LPL Frame Sequential (Max, 1920x1080 120Hz) 30 Security Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English,French,German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanisin Operating conditions 5°C - 4°CO, Max, Humidity 85%, Max, Atlitude 3000m Remote control 24 Watts per speaker 5W In the box AC power cord Remote control 22 AAA batteries Cuick Start Guide Networking LAN - control Yes Power Power consumption (min) 249W Power consumpt		0.73m - 7.63m (28.89in - 300.46in)
Lamp watts 330 Lamp iffe (hours) 3000 (Bight), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical Throw ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Connectivity Security bar,Kensington Lock,Password protected interface OSD / display languages English,French, German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Coperating conditions Security bar,Kensington Lock,Password protected interface OSD / display languages English,French, German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Control Data remote with laser and mouse function Speaker count Control	-	
Lamp life (hours) 3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+) Optical Throw ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Connectivity Connectivity Connectivity Signm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x WisB-A service, 1 x RJ45, 1 x V Hoger, 1 x RS222 Outputs 1 x Audio 3.5mm, 1 x U/Y Hoger, 1 x RS222 Optical 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480/xp, 576/xp, 120p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz	*	
Optical 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Connectivity Inputs 1 x HDMI/MHL, 1 x VGA, 1 x Mic Onnectivity S.mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x Connectivity UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 10 VHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Ouick Start Guide 0.5W Networking </th <th></th> <th></th>		
Throw ratio 0.782:1 Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Lens shift Yes - {{(downloads_link})} Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x JUSB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x JUSB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages 10 languages 10 languages Conditions 5°C - 40°C, Max, Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In th		3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+)
Projection distance (m) 0.5m - 5.2m Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Connectivity Connectivity Connectivity USB-A service, 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x JUSB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VGA, VGA, VGA, VGA, MAC 2D compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VGA, VGA, MAC 2D compatibility 102Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar.Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Spaaker count 2 Watts per speaker 5W In the box AC power cor		
Zoom type Fixed Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic Connections Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic Somm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, VGA, VGA, VGA, VGA, VGA, VGA,		
Focal length (mm) 11.66 Lens shift Vertical +10, % Native offset 100% Lens shift Yes - {[downloads_link}] Connectivity Inputs 1 x HDMI, 1 x HDM/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RI45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x SPDIF, 2 x Speaker General 32dB PC compatibility UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 1080p(50/60H2, 21 60(50/60H2)) 3D compatibility 120H2 Frame Sequential (Max. 1920x1080 120H2) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English, French, German, Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C ~ 4°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Spaker count 2 Watts per speaker SW In the box AC power cord Remote control Yes Power consumption (min) 249W Power cons		
Lens shift Vertical +10, % Native offset 100% Lens shift Yes - [(downloads_link]) Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic Connections Inputs 1 x HJMI, 1 x HDMI, MHL, 1 x VGA, 1 x Mic Softm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General 32dB Noise level (typical) 32dB PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, VGA, Mac 2D compatibility 2400/p, 576/p, 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 30 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar/Kensington Lock,Password protected interface OSD / display languages 10 languages: English, French, German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Vatts per speaker SW In the box		
Native offset 100% Lens shift Yes - [{downloads_link}] Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x R5232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 2460/p. 576/p. 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English,French,German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spaniah Operating conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Vatts per speaker 5W In the box AC power cord Remote control Networking LAN - control Yes Power consumption (max) 325W Weight 5.9kg <	* · ·	
Lens shift Yes - {{downloads_link}} Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic Connections Inputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x Moise level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480/p. 576/p. 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 3D 3D ready Security Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English,French,German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C ~ 4°°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W K Conver cord In the box AC power cord Remote control 2x AAA batteries Ouick Start Guide Yes Power Power consumption (min) 249W Power consumption (min) 249W Power consumption (max) 3		
Connectivity Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D Sompatibility 10 Languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish		
Connections Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 1080p(50/60Hz), 2160p(50/60Hz), 1080i(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English,French,German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C ~ 0°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide 2 Power consumption 0.5W (standby)		res - {{aownioaas_link}}
a.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480/p, 576/p, 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 2160p(50/60Hz), 2160p(50/60Hz), 30 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English, French, German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Attitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control Yes Power Oujck Start Guide Networking LAN - control LAN - control Yes Power consumption (min) 249W <th>2</th> <th></th>	2	
USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480/p, 576/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2180p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2180p(50/60Hz), 2180p(50/60Hz) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English,French,German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2 Networking LAN - control Yes Power Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions Net weight 5.9kg Dimensions (W x D x H) 392 x 281 x 129	Connections	
Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker General Noise level (typical) 32dB PC compatibility UHD, WUHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480/p, 576/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Beawer count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control Yes Power Power consumption 0.5W Power consumption 0.5W Power consumption (min) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
General 32dB PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480%, 576%, 720(50%0Hz), 1080(50%0Hz), 1080(50%0Hz), 1080(50%0Hz), 1080(50%0Hz), 2160(50%0Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Atlitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Power Power Power Power consumption 0.5W (stantdy) Power consumption (min) Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
Noise level (typical) 32dB PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480(p, 576(p, 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 2160p(50/60Hz)) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English,French,German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control Yes Power Quick Start Guide Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) Power consumption (min) Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480//p, 576//p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Attitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control LAN - control Yes Power 0.5W Power consumption 0.5W (standby) 100 ~ 240V, 50 ~ 60Hz Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
XGA, SVGA, VGA, Mac2D compatibility480//p, 576//p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)3D compatibility120Hz Frame Sequential (Max. 1920x1080 120Hz)3D3D readySecuritySecurity bar, Kensington Lock, Password protected interfaceOSD / display languages10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), SpanishOperating conditions5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000mRemote controlData remote with laser and mouse functionSpeaker count2Watts per speaker5WIn the boxAC power cord Remote controlNetworkingLAN - controlLAN - controlYesPower90Power consumption (standby)Power consumption (min)249WPower consumption (max)335WWeight5.9kgDimensions (W x D x H)392 x 281 x 129		
2D compatibility 480//p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar,Kensington Lock,Password protected interface OSD / display languages 10 languages: English,French,German,Italian,Japanese,Portuguese,Russian,Chin (simplified),Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control LAN - control Yes Power 0.5W Power consumption (min) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129	PC compatibility	
1080p(50/60Hz), 2160p(50/60Hz) 3D compatibility 120Hz Frame Sequential (Max. 1920x1080 120Hz) 3D 3D ready Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Attitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) 0.5W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129	2D compatibility	
3D 3D ready Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Attitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control LAN - control Yes Power 0.5W Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) 0.5W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129	3D compatibility	120Hz Frame Sequential (Max. 1920x1080 120Hz)
OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) 0.5W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129	3D	3D ready
English, French, German, Italian, Japanese, Portuguese, Russian, Chin (simplified), Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) 0.5W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129	Security	Security bar, Kensington Lock, Password protected interface
(simplified),Spanish Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control Networking AC power cord LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
Operating conditions 5° C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking L LAN - control Yes Power 7 Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		English, French, German, Italian, Japanese, Portuguese, Russian, Chine
Remote control Data remote with laser and mouse function Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Quick Start Guide Networking Yes Power Yes Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions S.9kg Dimensions (W x D x H) 392 x 281 x 129		
Speaker count 2 Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Quick Start Guide Networking Ves LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions S.9kg Dimensions (W x D x H) 392 x 281 x 129		
Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Quick Start Guide Networking LAN - control Yes Power Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions S.9kg Dimensions (W x D x H) 392 x 281 x 129		
In the box AC power cord Remote control 2x AAA batteries Quick Start Guide Networking LAN - control Yes Power Power consumption (standby) Power consumption (min) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions Net weight 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
Remote control 2x AAA batteries Quick Start Guide Networking LAN - control Yes Power Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions Net weight 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
2x AAA batteries Quick Start Guide Networking LAN - control Yes Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129	In the box	
Quick Start Guide Networking LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) Power consumption (min) Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
Networking LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
LAN - control Yes Power 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions S.9kg Dimensions (W x D x H) 392 x 281 x 129	Networking	
Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby) 249W Power consumption (min) 335W Weight and dimensions S.9kg Dimensions (W x D x H) 392 x 281 x 129	0	Yes
Power consumption 0.5W (standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 35W Net weight 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
(standby) 249W Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions 5.9kg Net weight 5.9kg Dimensions (W x D x H) 392 x 281 x 129		100 ~ 240V, 50 ~ 60Hz
Power consumption (min) 249W Power consumption (max) 335W Weight and dimensions	Power consumption	
Power consumption (max) 335W Weight and dimensions		249W
Weight and dimensions Net weight 5.9kg Dimensions (W x D x H) 392 x 281 x 129	,	
Net weight 5.9kg Dimensions (W x D x H) 392 x 281 x 129		
Dimensions (W x D x H) 392 x 281 x 129	<u> </u>	5.9kg
	-	0

Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 10122018042934