

DH351

High resolution presentations









- Lights on viewing 3600 ANSI lumens
- Easy connectivity HDMI, USB power
- Portable and lightweight
- Built-in audio

Project bright Full HD 1080p images with the DH351. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts ease of use with its single HDMI connection and built-in speaker. You can even use the USB power to connect and power HDMI dongles such as the Google Chromecast.



Specifications

Power

(standby)

Power supply
Power consumption

Gross weight

Net weight

Power consumption (min)

Power consumption (max)
Weight and dimensions

Dimensions (W x D x H)

Display/image Display technology DIP Resolution 1080p Full HD (1920x1080) Brightness 3,600 lumens Contrast ratio 22,000:1 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Keystone correction +/-40° vertical Uniformity 80% Screen size 0.71m ~ 7.65m (28" ~ 301") diagonal Lamp info Light source type Lamp Lamp watts 240 4000 (Bright), 15000 (Dynamic), 10000 (Eco) Lamp life hours (up to) Optical Throw ratio 1.47:1 ~ 1.62:1 Projection distance (m) 1m - 9.8m Zoom 1.1 Zoom type Manua Focal length (mm) 15.59mm~17.14mm/0.614"~0.675" Native offset Connectivity Connections Inputs 1 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A General

Noise level (typical) 26dB Noise level (max) 28dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 2D compatibility 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Security Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, OSD / display languages Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max Operating conditions humidity 85% Remote control Backlit home remote Speaker count Watts per speaker 5W In the box AC power cord Remote control 2x AAA batteries Basic user manual Optional wireless models HDCast Pro, WHD200

100 ~ 240V, 50 ~ 60Hz

0.5W

205W 295W

4.5 kg

2.8 kg

316 x 244 x 108



