

3751RK

Creative Touch 3 Series 75" interactive flat panel display









- Advanced interaction and collaboration TapCast Pro interactive wireless collaboration toolset
- Advanced touch technology Pen and finger recognition for a seamless experience
- Dual App mode Run two applications at the same time on the screen
- Safe and secure viewing experience Anti glare and anti finger print, low blue light and flicker free TUV certified

Robust collaboration, extensive connectivity options and a value-focused design. Combining the latest technology and packed with everything a classroom or business requires, the Creative Touch 3 Series delivers all the functionalities and processing power needed to create, educate and collaborate.

Easily access the front-facing ports for HDMI and USB connectivity. For wireless connectivity, Optoma's TapCast Pro allows up to four users to share content at the same time from their Windows, iOS, macOS, Chrome or Android device.



Specifications

Display Direct type LED Back light Direct type LED Size (diagonal) 75" Resolution 3840x2160	
Size (diagonal) 75"	
()	
Resolution 3840x2160	
Brightness 370	
Contrast ratio 1,200:1	
Contrast ratio (dynamic) 4,000:1	
Viewing angle 178°	
Response time 8ms	
Life 50,000 hours	
Display colours 1,070	
Speaker count 2	
Watts per speaker 15W	
Surface hardness 7H	
Glass Anti Glare + Anti Finger Print	
Ambient light sensor Yes	
Air gap 4,00mm	
Physical spec	
Dimensions (W x D x H) 1770 x 1071 x 109	
mm	
Wall-hanging screw spec M8*25mm	
VESA holes 800x400	
In the box European Standard Power Cord	
American Standard Power Cord British Standard Power Cord	
USB Cable	
HDMI Cable	
Writing Pen x2	
Remote Control	
Battery	
Pen holder/ Pen tray	
QSG	
Connections Inputs 3 x HDMI 2.0, 1 x VGA, 1 x	
3.5mm, 4 x USB2, 1 x USB 3.0, 1 x	
Outputs 1 x HDMI 2.0, 1 x S/PDIF,	
DIAE	1 x Addio 5.5min, 1 x
RJ45	
RJ45 Control 5 x USB-A (Interactive), 1 x	
Control 5 x USB-A (Interactive), 1 x	
Control 5 x USB-A (Interactive), 1 x Bezel size (top) 27,00mm	
Control 5 x USB-A (Interactive), 1 st Bezel size (top) 27,00mm Bezel size (left) 27,00mm	
Control 5 x USB-A (Interactive), 1 st Bezel size (top) 27,00mm Bezel size (left) 27,00mm Bezel size (right) 27,00mm	
Bezel size (top) 27,00mm Bezel size (left) 27,00mm Bezel size (right) 27,00mm Operating conditions 20% ~ 80% RH	
Bezel size (top) 27,00mm Bezel size (left) 27,00mm Bezel size (left) 27,00mm Bezel size (right) 27,00mm Operating conditions 20% ~ 80% RH Operating temperature 40°C	
Control 5 x USB-A (Interactive), 1 x Bezel size (top) 27,00mm Bezel size (left) 27,00mm Bezel size (right) 27,00mm Operating conditions 20% ~ 80% RH Operating temperature (max) 40°C	
Bezel size (top) 27,00mm Bezel size (left) 27,00mm Bezel size (right) 27,00mm Operating conditions 20% ~ 80% RH Operating temperature (max) 40°C Net weight 57 kg	
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 2 Bezel size (top)	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 x	K RS232
Control 5 x USB-A (Interactive), 1 2 Bezel size (top)	K RS232
Control 5 x USB-A (Interactive), 1 2 Bezel size (top)	K RS232
Control 5 x USB-A (Interactive), 1 2 Bezel size (top)	K RS232

16GB

Storage

