

ZH462

Eco-friendly compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -5000 lumens and IP6X certified
- Compact for easy installation 1.3x zoom, 360-degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The ZH462 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the ZH462 features an external power supply offering more reliability, portability and energy efficiency.

Specifications

EAN: 5055387667860, Colour: White

UPC: 796435447106, Colour: White Display/image DLP™ Display technology 1080p Full HD (1920x1080) Resolution **Brightness** 5.000 lumens Contrast ratio 3,000,000:1 Native aspect ratio 4:3,16:9,16:10 Aspect ratio - compatible 309 Keystone correction horizontal 30° Keystone correction - vertical Displayable colours (millions) 1073.4 Uniformity 75% Lamp info Light source type Laser LASER life 30,000 hours Optical

1.13:1 ~ 1.47:1

1m - 8m

1.3

Manual 16.90 ~ 21.61

116%

Focal length (mm)
Native offset
Connectivity

Throw ratio

Zoom type

Zoom

Projection distance (m)

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

 General
 29dB

 Noise level (typical)
 29dB

 Noise level (max)
 31dB

PC compatibility
FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility
NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) (50/60Hz) (5

 3D compatibility
 Yes (DLP 3D; F

 3D
 Full 3D

Security Security bar, Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese 24/7 operation Yes

360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

 Remote control
 Card style

 Speaker count
 1

 Watts per speaker
 15W

 In the box
 AC power cord Remote control

1x CR2025 battery Basic user manual UHDCast Pro

Optional wireless models

Power

Power supply External power supply, 100V \sim 240V, 50-60Hz Power consumption (standby) < 0.5W

Power consumption (standby) <0.5W
Power consumption (min) 128W
Power consumption (max) 205W

Weight and dimensions
Dimensions (W x D x H) mm

 Dimensions (W x D x H) mm
 274 x 216 x 108

 Gross weight
 4.6 kg

 Net weight
 3.4 kg



